



Break Sharp Edges: 0,1 mm

| | | | | | | | | | | | | |
|---|------|----------------|-----------|------------|----------------------|--|--|--|--|--|--|---|
| | | | | | | | | | | | | B |
| | | | | | | | | | | | | |
| Revision | Date | Description | | | | | | | | | |  |
| Engineered by: | | | Name: | Date: | Scale: 2:1 | | | | | | | |
| | | Designer: | Galba, J. | 17/07/2010 | | | | | | | | |
| | | Approved: | Galba, J. | 17/07/2010 | | | | | | | | |
| Project: | | | | | Material: Copper | | | | | | | |
| Miniature Model Hot Air Engine | | | | | Total Mass: 0.033 kg | | | | | | | |
| Title: | | | | | | | | | | | | A |
| Horizontal Stirling Engine | | | | | | | | | | | | |
| Heat Exchange Piston Exhaust | | | | | | | | | | | | |
|  InventorWizard.de/nl | | Drawingnumber: | | | | | | | Sheet: | | | |
| | | | | | | | | | 0001 | | | |
| | | Design State: | | | | | | | Drawing made with autodesk Inventor Revisions only permitted by CAD | | | |
| | | Released | | | | | | | | | | |

| | | | | | | | | | | | | | | | | | | |
|--|------------------|---------------|----------------|------------------|-------------------|--------------------|---------------------|---------------------|---------------------|---------------|----------------|------------------|-------------------|----------------------------|-----------------|------------------|-------------------|--------------|
| Corresponding symbols | | | | | | | | | | ▽ | ▼ | ▽▽ | ▼▼ | ▽▽▽ | ▼▼▼ | | | |
| Roughness Classes (NBN 88-02) (ISO 1302) | | | | | | | | | N11 | N10 | N9 | N8 | N7 | N6 | N5 | N4 | | |
| Roughness Value "Ra" in µm (NBN 88-02) (ISO 1302) | | | | | | | | | 25 | 12,5 | 6,3 | 3,2 | 1,6 | 0,8 | 0,4 | 0,2 | | |
| Allowable deviations for dimensions without tolerance indication (machined surfaces) | | | | | | | | | | | | | | | | | | |
| For measurements (deviations in mm) | | | | | | | | | Fillet and chamfers | | | | | Angles (in ° and ') | | | | |
| Accuracyclass (ISO 2768.1) | Dimensions in mm | | | | | | | | Dimensions in mm | | | | | Length of the shortest leg | | | | |
| | 0,5 to 3 | >3 to 6 | >6 to 30 | >30 to 120 | >120 to 400 | >400 to 1000 | >1000 to 2000 | >2000 to 4000 | 0,5 to 3 | >3 to 6 | >6 to 30 | >30 to 120 | >120 to 400 | to 10 | >10 to 50 | >50 to 120 | >120 to 400 | above 400 |
| f Fine | ±0,05 | ±0,05 | ±0,1 | ±0,15 | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±0,2 | ±0,5 | ±1 | ±2 | ±4 | ±1° | ±30' | ±20' | ±10' | ±5' |
| m Medium | ±0,1 | ±0,1 | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±1,2 | ±2 | | | | | | | | | | |
| c Rough | ±0,2 | ±0,3 | ±0,5 | ±0,8 | ±1,2 | ±2 | ±3 | ±4 | | | | | | ±1°30' | ±1° | ±30' | ±15' | ±10' |
| v Very Rough | - | ±0,5 | ±1 | ±1,5 | ±2,5 | ±4 | ±6 | ±8 | ±0,4 | ±1 | ±2 | ±4 | ±8 | ±3° | ±2° | ±1° | ±30' | ±20' |

This document is for educational purposes only and property of Inventor Wizard.
It shall not without our permission be altered, copied, used for manufacturing or
communicated to any other person or company.

